# SAFETY DATA SHEET.



Issuing date 11-May-2015 Revision Date 11-May-2015 Version 1.01

# 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product name SUPER SOLV

Recommended use of the chemical

and restrictions on use

Product code HT 18007

Product Type Extremely flammable aerosol

Synonyms None

Supplier's details

**Recommended Use Uses advised against**MULTI-PURPOSE SOLVENT.

No information available

Manufactured For: Hi-Tech Industries 33106 W. 8 Mile Farmington, MI 48336

Company Telephone: 248-358-2626

Chemical Emergency Phone INFOTRAC 1-352-323-3500 (International)

**Number** 1-800-535-5053 (North America)

# 2. HAZARDS IDENTIFICATION

#### Classification

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2B
Carcinogenicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Aspiration toxicity	Category 1
Flammable aerosols	Category 1
Gases under pressure	Compressed Gas

# GHS Label elements, including precautionary statements

#### **Emergency Overview**

#### DANGER

#### **Hazard Statements**

Causes skin irritation

Causes eye irritation

Suspected of causing cancer

May cause respiratory irritation. May cause drowsiness or dizziness

May be fatal if swallowed and enters airways

Extremely flammable aerosol

Contains gas under pressure; may explode if heated



Appearance Clear Physical state Aerosol Odor Light Vanilla Scent

#### **Precautionary Statements - Prevention**

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Wash face, hands and any exposed skin thoroughly after handling

Avoid breathing dust/fume/gas/mist/vapors/spray

Use only outdoors or in a well-ventilated area

Keep away from heat/sparks/open flames/hot surfaces. — No smoking

Do not spray on an open flame or other ignition source

Pressurized container: Do not pierce or burn, even after use

## **Precautionary Statements - Response**

If exposed or concerned: Get medical advice/attention

Specific treatment (see first aid on this label)

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention

IF ON SKIN: Wash with plenty of soap and water.

Take off contaminated clothing and wash before reuse

If skin irritation occurs: Get medical advice/attention

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a POISON CENTER or doctor/physician if you feel unwell

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

Do NOT induce vomiting

### **Precautionary Statements - Storage**

Store locked up

Store in a well-ventilated place. Keep container tightly closed

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

#### **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

#### Hazards not otherwise classified (HNOC)

None

#### Other information

· Toxic to aquatic life with long lasting effects

0% of the mixture consists of ingredient(s) of unknown toxicity

# 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Weight %*
PETROLEUM DISTILLATES	64742-89-8	60-70
PROPANE/ISOBUTANE/N-BUTANE	68476-86-8	10-20
XYLENE	1330-20-7	1-10
ETHYL BENZENE	100-41-4	1-10

<sup>\*</sup>The exact percentage (concentration) of composition has been withheld as a trade secret.

# 4. FIRST AID MEASURES

#### First aid measures for different exposure routes

Eye contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep

eye wide open while rinsing. If irritation persists, call a physician.

**Skin contact** Wash off immediately with soap and plenty of water while removing all contaminated

clothes and shoes. If symptoms persist, call a physician.

**Inhalation** Move to fresh air. If breathing is difficult, give oxygen. Artificial respiration and/or oxygen

may be necessary. If breathing has stopped, contact emergency medical services

immediately.

Ingestion Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a

physician or Poison Control Center immediately.

#### Most important symptoms/effects, acute and delayed

Main Symptoms Causes eye and skin irritation. Irritating to respiratory system. May cause drowsiness or

dizziness. May be fatal if swallowed and enters airways.

#### Indication of immediate medical attention and special treatment needed, if necessary

**Notes to physician** Treat symptomatically.

# 5. FIRE-FIGHTING MEASURES

### Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

**Unsuitable Extinguishing Media** Decomposition by contact with water may generate vapors which can be ignited by heat or open flame.

### Specific hazards arising from the chemical

No information available.

**Explosion Data** 

Sensitivity to Mechanical Impact none. Sensitivity to Static Discharge Yes.

### **Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

### 6. ACCIDENTAL RELEASE MEASURES

#### Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid contact with eyes, skin, and clothing. Avoid breathing vapors or mists. . Use with

adequate ventilation. Keep container away from heat, flames, and all other sources of

ignition.

**Environmental precautions** 

**Environmental precautions**Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate

in low areas. Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system. Do not allow material to contaminate ground water system.

Prevent product from entering drains.

#### Methods and materials for containment and cleaning up

**Methods for Containment**Absorb with earth, sand or other non-combustible material and transfer to containers for

later disposal. Stop leak if you can do it without risk.

Methods for cleaning up After cleaning, flush away traces with water. Clean contaminated surface thoroughly. Soak

up with inert absorbent material. Pick up and transfer to properly labeled containers. Take precautionary measures against static discharges. Prevent product from entering drains.

## 7. HANDLING AND STORAGE

#### Precautions for safe handling

Advice on safe handling Avoid contact with eyes. Avoid breathing vapors or mists. Contents under pressure. Do not

puncture or incinerate cans. Do not stick pin or any other sharp object into opening on top

of can.

#### Conditions for safe storage, including any incompatibilities

Technical measures/Storage

conditions

Keep away from open flames, hot surfaces and sources of ignition. Keep container tightly closed in a dry and well-ventilated place. Keep in properly labeled containers. Keep out of

the reach of children. Store locked up.

**Incompatible products**None known based on information supplied.

\_\_\_\_\_

Aerosol Level 3

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

# Control parameters

**Exposure Guidelines** 

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
PROPANE/ISOBUTANE/N-BUTANE	74-98-6: TWA: 1000 ppm	74-98-6:TWA: 1000 ppm	74-98-6:IDLH: 2100 ppm
68476-86-8	106-97-8: STEL: 1000 ppm	TWA: 1800 mg/m <sup>3</sup>	TWA: 1000 ppm
	75-28-5: STEL: 1000 ppm	(vacated) TWA: 1000 ppm	TWA: 1800 mg/m <sup>3</sup>
		(vacated) TWA: 1800 mg/m <sup>3</sup>	106-97-8:TWA: 800 ppm
		106-97-8: (vacated) TWA: 800	TWA: 1900 mg/m <sup>3</sup>
		ppm	75-28-5:TWA: 800 ppm
		(vacated) TWA: 1900 mg/m <sup>3</sup>	TWA: 1900 mg/m <sup>3</sup>
XYLENE	STEL: 150 ppm	TWA: 100 ppm	-
1330-20-7	TWA: 100 ppm	TWA: 435 mg/m <sup>3</sup>	
		(vacated) TWA: 100 ppm	
		(vacated) TWA: 435 mg/m <sup>3</sup>	
		(vacated) STEL: 150 ppm	
		(vacated) STEL: 655 mg/m <sup>3</sup>	
ETHYL BENZENE	TWA: 20 ppm	TWA: 100 ppm	IDLH: 800 ppm
100-41-4		TWA: 435 mg/m <sup>3</sup>	TWA: 100 ppm
		(vacated) TWA: 100 ppm	TWA: 435 mg/m <sup>3</sup>
		(vacated) TWA: 435 mg/m <sup>3</sup>	STEL: 125 ppm
		(vacated) STEL: 125 ppm	STEL: 545 mg/m <sup>3</sup>
		(vacated) STEL: 545 mg/m <sup>3</sup>	

ACGIH: (American Conference of Governmental Industrial Hygienists)

OSHA: (Occupational Safety & Health Administration) NIOSH IDLH: Immediately Dangerous to Life or Health

Other Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d

962 (11th Cir., 1992).

**Exposure controls** 

Engineering Measures Showers

Eyewash stations Ventilation systems.

### Individual protection measures, such as personal protective equipment

**Eye/Face Protection** Safety glasses with side-shields.

**Skin and body protection** Chemical resistant apron. Protective gloves.

**Respiratory protection** If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved

respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be

provided in accordance with current local regulations.

**Hygiene measures** Handle in accordance with good industrial hygiene and safety practice.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

#### Physical and chemical properties

Physical state Aerosol

AppearanceClearOdorLight Vanilla ScentColorNo information availableOdor ThresholdNo information available

Revision Date 11-May-2015

Based on propellant

Not applicable

<u>Property</u> <u>Values</u> <u>Remarks • Methods</u>

**pH** 0

Melting/freezing pointNo information availableBoiling point/boiling rangeNo information availableFlash Point-97 °C / -143 °F

Evaporation rate

No information available

**Evaporation rate**No information available **Flammability (solid, gas)**No information available

Flammability Limits in Air

upper flammability limitNo information availablelower flammability limitNo information availableVapor pressureNo information availableVapor densityNo information available

Specific Gravity 0.730

Water solubility Practically insoluble
Partition coefficient: n-octanol/waterNo information available
Autoignition temperature No information available

Decomposition temperatureNo information availableViscosityNo information availableExplosive propertiesNo information available

Other information

VOC Content(%) 100

#### 10. STABILITY AND REACTIVITY

#### Reactivity

No data available

#### **Chemical stability**

Stable under recommended storage conditions.

#### Possibility of hazardous reactions

None under normal processing.

### **Conditions to Avoid**

Extremes of temperature and direct sunlight.

#### **Incompatible Materials**

None known based on information supplied.

# **Hazardous Decomposition Products**

None known based on information supplied.

### 11. TOXICOLOGICAL INFORMATION

#### Information on likely routes of exposure

#### **Product Information**

**Inhalation** Vapors may irritate throat and respiratory system. May cause drownsiness and dizziness

based on components. May cause irritation of respiratory tract. Avoid breathing vapors or

mists.

**Eye contact** Irritating to eyes. Avoid contact with eyes.

**Skin contact** Irritating to skin. Avoid contact with skin.

Ingestion Aspiration into the lungs during swallowing may cause serious lung damage which may be

**Component Information** 

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation	
PETROLEUM DISTILLATES	=	= 3000 mg/kg ( Rabbit )	=	
64742-89-8				
XYLENE	= 3500 mg/kg (Rat)	> 4350 mg/kg (Rabbit)	= 29.08 mg/L (Rat) 4 h	
1330-20-7				
ETHYL BENZENE	-	= 15400 mg/kg (Rabbit)	-	
100-41-4				

### Information on toxicological effects

**Symptoms** Symptoms of overexposure may be headache, tiredness, nausea, and vomiting. Causes

respiratory irritation. Causes skin and eye irritation. Aspiration into the lungs during

swallowing may cause serious lung damage which may be fatal.

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Irritating to skin. Eye damage/irritation Irritating to eyes. Sensitization None known. **Germ Cell Mutagenicity** None known.

Carcinogenicity The table below indicates whether each agency has evaluated a listed ingredient as a

carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
XYLENE	-	Group 3	-	-
1330-20-7		•		
ETHYL BENZENE	A3	Group 2B	-	-
100-41-4		·		

ACGIH: (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC: (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

Group 3 - Not Classifiable as to Carcinogenicity in Humans OSHA: (Occupational Safety & Health Administration)

X - Present

Reproductive toxicity

Specific target organ systemic toxicity (single exposure)

Specific target organ systemic toxicity (repeated exposure)

**Target Organ Effects** 

**Neurological effects** 

This product does not contain any known or suspected reproductive hazards.

May cause respiratory irritation. May cause drowsiness and dizziness.

No information available.

Central nervous system, Eyes, Respiratory system, Skin.

Intentional misuse by deliberately concentrating and inhaling contents may be harmful or

**Aspiration hazard** May be fatal if swallowed and enters airways.

### Numerical measures of toxicity - Product Information

**Unknown Acute Toxicity** 0% of the mixture consists of ingredient(s) of unknown toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 36212 mg/kg 11381 mg/kg **ATEmix (dermal)** ATEmix (inhalation-dust/mist) 12.5 mg/l

# 12. ECOLOGICAL INFORMATION

# **Ecotoxicity**

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to microorganisms	Toxicity to daphnia and other aquatic invertebrates
---------------	-------------------	------------------	----------------------------	---

DETDOLEUM DICTUL ATEC	4700 // FOF0			
PETROLEUM DISTILLATES	J	-	-	-
64742-89-8	Pseudokirchneriella			
	subcapitata 72h			
PROPANE/ISOBUTANE/N-	<del>-</del>	-	-	-
BUTANE				
68476-86-8				
XYLENE	-	13.1 - 16.5 mg/L LC50	-	0.6 mg/L LC50 Gammarus
1330-20-7		Lepomis macrochirus 96h		lacustris 48h 3.82 mg/L
		flow-through 13.5 - 17.3		EC50 water flea 48h
		mg/L LC50 Oncorhynchus		
		mykiss 96h 2.661 - 4.093		
		mg/L LC50 Oncorhynchus		
		mykiss 96h static 23.53 -		
		29.97 mg/L LC50		
		Pimephales promelas 96h		
		static 30.26 - 40.75 mg/L		
		LC50 Poecilia reticulata 96h		
		static 7.711 - 9.591 mg/L		
		LC50 Lepomis macrochirus		
		96h static 13.4 mg/L LC50		
		Pimephales promelas 96h		
		flow-through 19 mg/L LC50		
		Lepomis macrochirus 96h		
		780 mg/L LC50 Cyprinus		
		carpio 96h semi-static 780		
		mg/L LC50 Cyprinus carpio		
		96h		
ETHYL BENZENE	4.6 mg/L EC50	11.0 - 18.0 mg/L LC50	-	1.8 - 2.4 mg/L EC50 Daphnia
100-41-4	Pseudokirchneriella	Oncorhynchus mykiss 96h		magna 48h
	subcapitata 72h 438 mg/L	static 7.55 - 11 mg/L LC50		
	EC50 Pseudokirchneriella	Pimephales promelas 96h		
	subcapitata 96h 2.6 - 11.3	flow-through 9.1 - 15.6 mg/L		
	mg/L EC50	LC50 Pimephales promelas		
	Pseudokirchneriella	96h static 32 mg/L LC50		
	subcapitata 72h static 1.7 -	Lepomis macrochirus 96h		
	7.6 mg/L EC50	static 4.2 mg/L LC50		
	Pseudokirchneriella	Oncorhynchus mykiss 96h		
	subcapitata 96h static	semi-static 9.6 mg/L LC50		
		Poecilia reticulata 96h static		

### Persistence and degradability

No information available.

### **Bioaccumulation**

No information available.

Chemical Name	log Pow
PROPANE/ISOBUTANE/N-BUTANE	2.8
68476-86-8	
XYLENE	3.15
1330-20-7	
ETHYL BENZENE	3.118
100-41-4	

Other adverse effects No information available

# 13. DISPOSAL CONSIDERATIONS

### **Waste treatment**

Waste Disposal Methods This material, as supplied, is a hazardous waste according to federal regulations (40 CFR

261).

Contaminated packaging Do not re-use empty containers.

### 14. TRANSPORT INFORMATION

**DOT Ground** CONSUMER COMMODITY ORM-D

or

LIMITED QUANTITY

IATA UN1950, AEROSOLS, FLAMMABLE, 2.1, LTD. QTY.

IMDG UN1950, AEROSOLS, 2.1, LTD. QTY.

### 15. REGULATORY INFORMATION

# **International Inventories**

Chemical Name	TSCA	DSL/NDSL	EINECS/ELI NCS	ENCS	IECSC	KECL	PICCS	AICS
PETROLEUM DISTILLATES	Х	Х	Х	Not listed	Х	Х	Х	Х
PROPANE/ISOBUTAN E/N-BUTANE	Х	Х	Х	Not listed	Х	Х	Х	Х
XYLENE	Х	X	X	Х	Х	Х	Х	Х
ETHYL BENZENE	Х	X	X	Х	Х	Х	Х	Х

#### Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances

CHINA - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

# U.S. Federal Regulations

#### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	CAS-No	Weight %*	SARA 313 - Threshold Values %
XYLENE - 1330-20-7	1330-20-7	1-10	1.0
ETHYL BENZENE - 100-41-4	100-41-4	1-10	0.1

## SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	Yes
Reactive Hazard	no

Revision Date 11-May-2015

Clean Water Act

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42):

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
XYLENE 1330-20-7	100 lb			Х
ETHYL BENZENE 100-41-4	1000 lb	X	X	Х

# **CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302):

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances	RQ
		RQs	
XYLENE	100 lb		RQ 100 lb final RQ
1330-20-7			RQ 45.4 kg final RQ
ETHYL BENZENE	1000 lb		RQ 1000 lb final RQ
100-41-4			RQ 454 kg final RQ

### **U.S. State Regulations**

#### **California Proposition 65**

This product contains the following Proposition 65 chemicals:

Chemical Name	California Prop. 65	
ETHYL BENZENE - 100-41-4	Carcinogen	
BENZENE - 71-43-2	Carcinogen Developmental Male Reproductive	
TOLUENE - 108-88-3	Developmental Female Reproductive	

#### **U.S. State Right-to-Know Regulations**

Chemical Name	New Jersey	Massachusetts	Pennsylvania
PETROLEUM DISTILLATES			Х
64742-89-8			
XYLENE	X	X	X
1330-20-7			
ETHYL BENZENE	X	X	X
100-41-4			

**EPA Pesticide Registration Number** Not applicable

## <u>Canada</u>

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.



# 16. OTHER INFORMATION

NFPA Health Hazard 2 Flammability 4 Instability 0 Physical and chemical hazards -

#### HT 18007 SUPER SOLV CLEANER.

Revision Date 11-May-2015

HMIS Health Hazard 2 Flammability 4 Physical Hazard 1 Personal protection B

Prepared By American Jetway

34136 Myrtle Street Wayne, MI 48184

Tel.734-721-5930

Issuing date11-May-2015Revision Date11-May-2015

**Revision Note** 

No information available

Disclaimer

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

**End of Safety Data Sheet**